

US009636928B2

(12) United States Patent

Noell

(10) Patent No.: US 9,636,928 B2

(45) **Date of Patent:** May 2, 2017

(54) APPARATUS FOR THE PRINTING AND RADIATION TREATMENT OF A CURVED SURFACE OF AN OBJECT

(71) Applicant: HEIDELBERGER

DRUCKMASCHINEN AG,

Heidelberg (DE)

(72) Inventor: Matthias Noell, Weiterstadt (DE)

(73) Assignee: Heidelberger Druckmaschinen AG,

Heidelberg (DE)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 2 days.

(21) Appl. No.: 14/627,171

(22) Filed: Feb. 20, 2015

(65) Prior Publication Data

US 2015/0231897 A1 Aug. 20, 2015

(30) Foreign Application Priority Data

Feb. 20, 2014 (DE) 10 2014 002 710

(51) Int. Cl. *B41J 2/01 B41J 3/407*

(2006.01) (2006.01)

B41J 29/12 (2006.01) **B41J 11/00** (2006.01)

(52) U.S. Cl.

CPC *B41J 11/002* (2013.01); *B41J 2/01* (2013.01); *B41J 3/4073* (2013.01); *B41J*

29/12 (2013.01)

(58) Field of Classification Search

CPC B41J 2/01; B41J 3/4073; B41J 29/12 See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

7,350,890	B2	4/2008	Baird et al.
7,370,955	B2	5/2008	Yokoyama et al.
2003/0234848	A1*	12/2003	Ishikawa B41J 2/2117
			347/102
2007/0062383	A1*	3/2007	Gazeau et al 101/35
2008/0204536	A1*	8/2008	Suzuki B41J 11/002
			347/102
2016/0167399	A1*	6/2016	Ohnishi B41J 2/01
			347/102

FOREIGN PATENT DOCUMENTS

DE 102009058212 A1 6/2011 DE 102010034780 A1 2/2012 (Continued)

Primary Examiner — Kristal Feggins Assistant Examiner — Kendrick Liu

(74) Attorney, Agent, or Firm — Laurence A. Greenberg; Werner H. Stemer; Ralph E. Locher

(57) ABSTRACT

An apparatus for the printing and radiation treatment of a curved surface of an object, such as a body part, includes a printing unit, preferably an inkjet print head, a radiation unit, preferably a UV dryer, and a movement unit, preferably a robot, either for moving the printing unit and the radiation unit at a working distance along the surface or for moving the object at a working distance along the printing unit and the radiation unit. A shielding unit can be adjusted and/or deformed relative to the printing unit and/or relative to the radiation unit and during the printing. Scattered radiation is shielded and damage to the printing unit is prevented as a result of the special configuration of the shielding unit.

15 Claims, 5 Drawing Sheets

